

SAFETY DATA SHEETS

This SDS packet was issued with item:

074290680

The safety data sheets (SDS) in this packet apply to the individual products listed below. Please refer to invoice for specific item number(s).

074290573 074290581 074290599 074290607 074290615 074290623 074290672 074290698 074290706 074290714
074290722

The safety data sheets (SDS) in this packet apply to one or more components included in the items listed below. Items listed below may require one or more SDS. Please refer to invoice for specific item number(s).

074290565 074290896 074290904

**NX3 Nexus Third Generation
PASTE PRODUCTS**

Light Cure and Dual Cure

1 - IDENTIFICATION

Manufacturer: Kerr Corporation
Address: 1717 West Collins Avenue
City, State, Zip: Orange, CA 92867-5422
Telephone: 1-800-KERR-123
Emergency: Chemtrec 1-800-424-9300
Date Prepared: January 31, 2007

2 - COMPOSITION INFORMATION

Hazardous Ingredients

	<u>CAS#</u>	<u>PEL</u>	<u>TLV</u>	<u>%</u>
Uncured Methacrylate Ester Monomers	109-16-0	N/A	N/A	20-40

Other Ingredients

Non-hazardous inert mineral fillers, non-hazardous activators and stabilizers and radiopaque agent.

3 - PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point: N/D
Specific Gravity (H₂O = 1): 2.0 - 2.5
Vapor Pressure (mm Hg): N/D
Vapor Density (AIR = 1): N/D
Solubility in Water: Insoluble
Reactivity in Water: N/A
Appearance and Odor: Colored Paste with fruity ester-like odor.

4 - FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used): N/D
Flammable Limits: LEL: N/A UEL: N/D
Extinguishing Media: Chemical foam, CO₂, dry chemical
Special Fire Fighting Procedures: Wear self-contained breathing apparatus.
Unusual Fire and Explosion Hazards: Heat can cause polymerization with rapid release of energy.

5 - REACTIVITY DATA

Stability: Stable if stored as directed.
Conditions to Avoid: Heat, light, aging and sources of contamination.
Incompatibility (Material to Avoid): Reducing and oxidizing agents, peroxides and amines.
Hazardous Decomposition Products: Oxides of carbon
Hazardous Polymerization: May occur if contaminated or heated.

6 - HEALTH HAZARD DATA

Routes of Entry:
Skin: Prolonged or repeated exposure to uncured material may cause irritation or skin rash especially in sensitive individuals.
Eyes: May cause irritation and damage if not removed promptly.
Inhalation: Prolonged or excessive inhalation may cause respiratory tract irritation.
Ingestion: Uncured material may be harmful if swallowed.
Carcinogenicity - NTP: No
IARC Monographs: No **OSHA Regulated Carcinogen:** No

7 - EMERGENCY FIRST AID PROCEDURES

Skin: Wash thoroughly with soap and water.
Eyes: Flush with water for 15 minutes including under eyelids.
Inhalation: Remove to fresh air - get medical attention if discomfort persists.
Ingestion: Rinse mouth out with water - do not induce vomiting. Seek medical attention.

8 - PRECAUTIONS FOR SAFE HANDLING & USE

Steps to be taken in case material is released or spilled: Absorb spills with inert material. Keep spilled material out of sewers.
Waste Disposal Method: Unpolymerized (uncured) material may be RCRA hazardous waste. Incinerate uncured material in accordance with all Federal, State and local regulations.
Precautions to be taken in handling and storing: Store in a cool, dry place away from heat light and ignition.

9 - CONTROL MEASURES

Respiratory Protection (Specify Type): Avoid prolonged or excessive breathing of vapors of uncured material.
VENTILATION:
Local Exhaust: Good general ventilation should be sufficient to control airborne levels of vapors released by uncured material.
Mechanical (General): Good general ventilation recommended.
Protective Gloves: Impervious rubber gloves recommended when contacting uncured material.
Eye Protection: Safety glasses recommended.
Other Protective Clothing or Equipment: N/A
Work/Hygiene Practices: Handle in accordance with good personal hygiene and safety practices. These practices include avoiding unnecessary exposure to uncured material.

10 - TRANSPORTATION INFORMATION

Not DOT regulated.

11 - SPECIAL INFORMATION

HMS (Hazardous Material Identification System) Rating:
H2 F1 R2 PPE-Gloves and safety glasses. Hazard information relates only to uncured material.
[HMS Index: 4 - Severe Hazard; 3 - Serious Hazard; 2 - Moderate Hazard; 1 - Slight Hazard; 0 - Minimum Hazard]

Note: Hazard information contained on this MSDS form relates only to material in its uncured state. Thorough biocompatibility and toxicity testing of the cured material and its extracts have demonstrated that the material is non-toxic.

Note: This MSDS was prepared in accordance with the requirements of the OSHA Hazard Communication Standard (29 CFR 1910.1200) and is to be used only for this product. The information in this MSDS is, to the best of our knowledge, believed to be accurate.